

HCS-5300MX

Digital IR Conference Room Switcher



Features

- Perfect solution for selectively combining or separating meeting rooms
- Flexibly and discretionary - according to situational conditions
- **4 inputs × 4 group outputs** Digital IR Matrix Switcher, 5 outputs per group
- Each HCS-5300MX can be connected to 10 transceivers at the most
- Able to merge up to 4 meeting rooms
- LCD to display real-time operation
- Front panel button control , easy to switch manually
- 2U high, full rack width

Controls and Indicators

- Graphic LCD with back-lighting displays configuration
- Four buttons for configuration
- Power switch with indicator
- Input channel selectors with indicators (4 inputs)

- Infrared signal output group selectors with indicators (4 groups, 5 outputs per group)

Interconnections

- Transceiver inputs from HCS-5300M Digital IR Wireless Conference System Main Unit: 4 channels input via 6P-DIN sockets
- Transceiver outputs to HCS-5300T Transceiver: 4 groups of infrared signal output via 6P-DIN sockets, 5 outputs per group
- 1 × RS232 port for connection to intelligent central control system and system diagnosis

Technical Specifications

Electrical

Power supply.....AC 100 V-120 V 60 Hz or AC 220 V-240 V 50 Hz
 Power consumption.....15 W
 Max. consumption.....430 W

Mechanical

Mounting.....Tabletop or mounted in a 19" rack
 Dimensions (h x w x d)
 For table use, with feet.....99 × 430 × 325 mm
 For 19" rack use, with brackets.....89 × 478 × 350 mm
 Weight.....10.6 kg
 Color.....White (PANTONE 420 C)

Ordering Information

HCS-5300MX.....Digital IR Conference Room Switcher

